




Compact wireless temp. sensor		Passive (no battery)	PTS-150M 
Temp range	:	- 25 C to +150 C	
Accuracy	:	±1 C	
Samplings rate	:	default 20s	
Wireless frequency	:	433MHz	
Transmission range	:	≤150m (open area)	
Power: Induction activate current	:	≥5A	
Installation mode	:	Bundled	
Dimension	:	26mm*22.5*9.9mm	

PTS-150S 	Wireless temp sensor (Strap)		Passive
	Temp. test range	:	-25 C+150 C
	Accuracy	:	±1 C
	Samplings rate	:	default 20s
	Wireless frequency	:	433MHz
	Transmission range	:	≤200m (open area)
	Power: Induction activate current	:	≥5A
	Installation mode	:	Bundled
	Dimension	:	35mm*21mm*13.7mm
Band length	:	385mm	

Wireless temperature sensor		With battery	BTS-150 
Temp. test range	:	- 25 C to +150 C	
Accuracy	:	±1 C	
Samplings rate:	:	default 5 min	
Wireless frequency	:	433MHz	
Transmission range	:	≤200m (open area)	
Power:	:	Lithium battery	
Installation:	:	bolted and magnetic	
Dimension:	:	62mm x 45mm x 22.5mm	

WTS-80RH 	Wireless Temp. & Humidity sensor With battery		
	Temp Range	:	-40 C to +80 C Accuracy: ±2 C
	RH Range	:	5 % ~99 % RH Accuracy: 3 % RH
	Samplings rate	:	default 5 min
	Wireless frequency	:	433MHz
	Transmission range	:	≤200m (open area)
	Power	:	Lithium battery
	Installation:	:	Magnetic rail for easy onsite installation
Dimension:	:	55mm x 29.5mm	